



ZEMA

TIGES DE FORAGE DRILL PIPES



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA



ACCESSOIRES
ACCESSORIES



TIGES DE FORAGE
DRILL PIPES



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TIGES STANDARD / STANDARD PIPES

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
70	4.0	1000	ACT/NWY/MAYJR DQ	55	9.9
70	4.0	1000	RD50-6	55	9.9
70	4.0	1500	ACT/NWY/MAYJR DQ	55	13.1
70	4.0	1500	RD50-6	55	13.6
70	4.0	3000	ACT/NWY/MAYJR DQ	55	22.9
70	4.0	3000	RD50-6	55	22.9
76	4.0	500	2"3/8 API REG	65	8.4
76	4.0	750	2"3/8 API REG	65	10.1
76	4.0	1000	2"3/8 API REG	65	11.8
76	4.0	1500	2"3/8 API REG	65	15.2
76	4.0	1800	2"3/8 API REG	65	17.2
76	4.0	1900	2"3/8 API REG	65	17.9
76	4.0	2000	2"3/8 API REG	65	18.6
76	4.0	3000	2"3/8 API REG	65	25.4
76	6.3	500	2"3/8 API REG	65	8.7
76	6.3	600	2"3/8 API REG	65	9.8
76	6.3	750	2"3/8 API REG	65	11.4
76	6.3	1000	2"3/8 API REG	65	14.1
76	6.3	1200	2"3/8 API REG	65	16.3
76	6.3	1350	2"3/8 API REG	65	17.9
76	6.3	1500	2"3/8 API REG	65	19.5
76	6.3	1600	2"3/8 API REG	65	20.6
76	6.3	1700	2"3/8 API REG	65	21.7
76	6.3	1800	2"3/8 API REG	65	22.7
76	6.3	1830	2"3/8 API REG	65	23.1
76	6.3	1850	2"3/8 API REG	65	23.3
76	6.3	1900	2"3/8 API REG	65	23.8
76	6.3	2000	2"3/8 API REG	65	24.9
76	6.3	2100	2"3/8 API REG	65	26
76	6.3	3000	2"3/8 API REG	65	35.7
76	6.3	3048	2"3/8 API REG	65	36.2
76	6.3	4000	2"3/8 API REG	65	46.5
76	6.3	4500	2"3/8 API REG	65	51.9
76	6.3	5000	2"3/8 API REG	65	57.3
76	6.3	6000	2"3/8 API REG	65	68.1
76	8.8	1000	2"3/8 API REG	65	17.1
76	8.8	1500	2"3/8 API REG	65	24.4
76	8.8	2000	2"3/8 API REG	65	31.7
76	8.8	3000	2"3/8 API REG	65	46.3

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TIGES STANDARD / STANDARD PIPES

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
89	4.0	500	2"3/8 API REG	65	9.6
89	4.0	1000	2"3/8 IF	65	14.5
89	4.0	1000	2"3/8 API REG	65	13.8
89	4.0	1000	2"7/8 API REG	65	14.6
89	4.0	1000	RD70-4	65	13.0
89	4.0	1500	2"3/8 IF	65	18.7
89	4.0	1500	2"3/8 API REG	65	18.0
89	4.0	1500	2"7/8 API REG	65	18.8
89	4.0	1500	RD70-4	65	17.2
89	4.0	2000	2"3/8 IF	65	22.9
89	4.0	2000	2"3/8 API REG	65	22.2
89	4.0	2000	2"7/8 API REG	65	23.0
89	4.0	2000	RD70-4	65	21.4
89	4.0	3000	2"3/8 IF	65	31.3
89	4.0	3000	2"3/8 API REG	65	30.5
89	4.0	3000	2"7/8 API REG	65	31.4
89	4.0	3000	RD70-4	65	29.9
89	6.3	500	2"3/8 API REG	65	10.9
89	6.3	1000	2"3/8 IF	65	17.8
89	6.3	1000	2"3/8 API REG	65	17.3
89	6.3	1000	2"7/8 API REG	65	18.0
89	6.3	1500	2"3/8 IF	65	24.2
89	6.3	1500	2"3/8 API REG	65	23.7
89	6.3	1500	2"7/8 API REG	65	24.4
89	6.3	2000	2"3/8 IF	65	30.6
89	6.3	2000	2"3/8 API REG	65	30.1
89	6.3	2000	2"7/8 API REG	65	30.8
89	6.3	2500	2"3/8 API REG	65	36.5
89	6.3	3000	2"3/8 IF	65	43.4
89	6.3	3000	2"3/8 API REG	65	42.9
89	6.3	3000	2"7/8 API REG	65	43.6
89	6.3	3000	RD70-4	65	42.3
89	6.3	4000	2'3/8 IF	65	56.2
89	6.3	4000	2"3/8 API REG	65	55.7
89	6.3	5000	2"3/8 IF	65	69.0
89	6.3	5000	2"3/8 API REG	65	68.5
89	6.3	6000	2"3/8 IF	65	81.8
89	6.3	6000	2"3/8 API REG	65	81.7
89	6.3	6000	2"7/8 API REG	65	82.0

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TIGES STANDARD / STANDARD PIPES

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
89	8.8	500	2"3/8 API REG	65	11.8
89	8.8	1000	2"3/8 API REG	65	19.8
89	8.8	1500	2"3/8 API REG	65	27.8
89	8.8	2000	2"3/8 API REG	65	35.7
89	8.8	3000	2"3/8 API REG	65	51.7
89	8.8	4000	2"3/8 API REG	65	67.7
89	8.8	5000	2"3/8 API REG	65	83.6
89	8.8	6000	2"3/8 API REG	65	99.6
102	6.3	1000	2"7/8 API REG	75	23.6
102	6.3	1500	2"7/8 API REG	75	31.0
102	6.3	2000	2"7/8 API REG	75	38.4
102	6.3	3000	2"7/8 API REG	75	53.2
102	6.3	4000	2"7/8 API REG	75	68.0
102	6.3	5000	2"7/8 API REG	75	82.8
102	6.3	6000	2"7/8 API REG	75	97.6
114	6.3	500	3"1/2 API REG	95	18.0
114	6.3	500	3"1/2 IF	95	18.5
114	6.3	750	3"1/2 API REG	95	22.2
114	6.3	750	3"1/2 IF	95	22.7
114	6.3	1000	3"1/2 API REG	95	26.4
114	6.3	1000	3"1/2 IF	95	26.9
114	6.3	1500	3"1/2 API REG	95	34.8
114	6.3	1500	3"1/2 IF	95	35.3
114	6.3	2000	3"1/2 API REG	95	43.2
114	6.3	2000	3"1/2 IF	95	43.7
114	6.3	3000	3"1/2 API REG	95	60.0
114	6.3	3000	3"1/2 IF	95	60.5
114	6.3	4000	3"1/2 API REG	95	76.8
114	6.3	4000	3"1/2 IF	95	77.3
114	6.3	5000	3"1/2 API REG	95	93.6
114	6.3	5000	3"1/2 IF	95	94.1
114	6.3	6000	3"1/2 API REG	95	110.4
114	6.3	6000	3"1/2 IF	95	110.9
114	8.8	500	3"1/2 API REG	95	19.4
114	8.8	500	3"1/2 IF	95	19.9
114	8.8	750	3"1/2 API REG	95	25.1
114	8.8	750	3"1/2 IF	95	25.6
114	8.8	1000	3"1/2 API REG	95	30.8

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TIGES STANDARD / STANDARD PIPES

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
114	8.8	1000	3 1/2"IF	95	31.3
114	8.8	1500	3 1/2" API REG	95	42.3
114	8.8	1500	3 1/2"IF	95	42.8
114	8.8	2000	3 1/2"API REG	95	53.7
114	8.8	2000	3 1/2"IF	95	54.2
114	8.8	3000	3 1/2"API REG	95	76.6
114	8.8	3000	3 1/2"IF	95	77.1
114	8.8	4000	3 1/2"API REG	95	99.5
114	8.8	4000	3 1/2"IF	95	100
114	8.8	5000	3 1/2" API REG	95	122.4
114	8.8	5000	3 1/2"IF	95	122.9
114	8.8	6000	3 1/2"API REG	95	145.3
114	8.8	6000	3 1/2"IF	95	145.8
127	6.3	1000	3 1/2"IF	95	35.5
127	6.3	1000	3 1/2"API REG	95	36.5
127	6.3	1500	3 1/2"IF	95	44.9
127	6.3	1500	3 1/2"API REG	95	45.9
127	6.3	2000	3 1/2"IF	95	54.3
127	6.3	2000	3 1/2"API REG	95	55.3
127	6.3	3000	3 1/2"IF	95	73.1
127	6.3	3000	3 1/2"API REG	95	74.1
127	6.3	4000	3 1/2"IF	95	91.9
127	6.3	4000	3 1/2"API REG	95	92.9
127	6.3	5000	3 1/2"IF	95	110.7
127	6.3	5000	3 1/2"API REG	95	111.7
127	6.3	6000	3 1/2"IF	95	129.5
127	6.3	6000	3 1/2"API REG	95	130.5
127	8.8	1000	3 1/2"IF	95	39.8
127	8.8	1000	3 1/2"API REG	95	41.1
127	8.8	1500	3 1/2"IF	95	52.6
127	8.8	1500	3 1/2"API REG	95	53.9
127	8.8	2000	3 1/2"IF	95	65.5
127	8.8	2000	3 1/2"API REG	95	66.8
127	8.8	3000	3 1/2"IF	95	91.2
127	8.8	3000	3 1/2"API REG	95	92.5
127	8.8	4000	3 1/2"IF	95	116.9
127	8.8	4000	3 1/2"API REG	95	118.2
127	8.8	5000	3 1/2"IF	95	142.6

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TIGES STANDARD / STANDARD PIPES

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
127	8.8	6000	3 1/2" IF	95	168.3
127	8.8	6000	3 1/2" API REG	95	169.6
140	8.8	500	3 1/2" IF	120	33.2
140	8.8	500	4 1/2" API REG	120	32.3
140	8.8	1000	3 1/2" IF	120	47.4
140	8.8	1000	3 1/2" API REG	120	48.6
140	8.8	1000	4 1/2" API REG	120	46.5
140	8.8	1500	3 1/2" IF	120	61.6
140	8.8	1500	3 1/2" API REG	120	62.8
140	8.8	1500	4 1/2" API REG	120	60.7
140	8.8	2000	3 1/2" IF	120	75.8
140	8.8	2000	3 1/2" API REG	120	77
140	8.8	2000	4 1/2" API REG	120	74.9
140	8.8	3000	3 1/2" IF	120	104.2
140	8.8	3000	3 1/2" API REG	120	105.4
140	8.8	3000	4 1/2" API REG	120	103.3
140	8.8	4000	3 1/2" IF	120	132.6
140	8.8	4000	3 1/2" API REG	120	133.8
140	8.8	4000	4 1/2" API REG	120	131.7
140	8.8	5000	3 1/2" IF	120	161
140	8.8	5000	3 1/2" API REG	120	162.2
140	8.8	5000	4 1/2" API REG	120	160.1
140	8.8	6000	3 1/2" IF	120	189.4
140	8.8	6000	3 1/2" API REG	120	190.6
140	8.8	6000	4 1/2" API REG	120	188.5

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TIGES STANDARD / STANDARD PIPES

50 CRAELIUS

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
50	6.3	1500	CR50	42	11
50	6.3	3000	CR50	42	21.1



60 CRAELIUS

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
60	6.3	500	CR60	50	6.7
60	6.3	750	CR60	50	8.8
60	6.3	1000	CR60	50	10.9
60	6.3	1500	CR60	50	15.1
60	6.3	2000	CR60	50	19.3
60	6.3	3000	CR60	50	27.7



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

ATLAS COPCO

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD BOX	THREAD PIN	PLATS FLATS (mm)	POIDS WEIGHT (kg)
ATLAS COPCO						
CM (695/760/780)						
76	6.3	2700	2"Z	2"Z	CM	33.6
76	6.3	4000	2"Z	2"Z	CM	45.5
76	6.3	5000	2"Z	2"Z	CM	56.3
76	8.8	2900	2 3/8" API REG	2"Z	CM	46.6
76	8.8	4000	2"Z	2"Z	CM	61.6
76	8.8	4600	2 3/8" API REG	2"Z	CM	71.4
76	12.5	4000	2"Z	2"Z	CM	80.6
89	6.3	4000	2 1/2"Z	2 1/2"Z	CM	57.8
89	6.3	5000	2 1/2"Z	2 1/2"Z	CM	70.6
89	8.8	2400	3 1/2" API REG	2 1/2"Z	CM	49.6
89	8.8	2700	2 3/8" API REG	2 1/2"Z	CM	60
89	8.8	2700	2 3/8" API REG	2 1/2"Z	CM	49.6
89	8.8	4400	3 1/2" API REG	2 1/2"Z	CM	81.5
89	8.8	4600	2 3/8" API REG	2 1/2"Z	CM	80
102	6.3	2435	2 1/2"Z	2 1/2"Z	CM	44
102	6.3	4000	2 1/2"Z	2 1/2"Z	CM	66.9
102	6.3	5000	2 1/2"Z	2 1/2"Z	CM	81.7
102	8.8	2700	3 1/2" API REG	2 1/2"Z	CM	65.4
102	8.8	4400	3 1/2" API REG	2 1/2"Z	CM	99.6
102	12.5	4000	3 1/2" API REG	2 1/2"Z	CM	118



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

ATLAS COPCO

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
ATLAS COPCO					
ROC (F6/ L6/ L8/ SMARTROC/ FLEXIROC)					
76	4	4000	2 3/8" API REG	ROC	36.5
76	6.3	1800	2 3/8" API REG	ROC	26.8
76	6.3	3700	2 3/8" API REG	ROC	47.3
76	6.3	4000	2 3/8" API REG	ROC	50.5
76	6.3	5000	2 3/8" API REG	ROC	61.3
76	6.3	6000	2 3/8" API REG	ROC	72.1
89	6.3	4000	2 3/8" API REG	ROC	62.5
89	6.3	5000	2 3/8" API REG	ROC	75.3
89	6.3	6000	2 3/8" API REG	ROC	88.1
89	8.8	4000	2 3/8" API REG	ROC	73.9
89	8.8	5000	2 3/8" API REG	ROC	89.9
89	8.8	6000	2 3/8" API REG	ROC	105.9
89	8.8	6000	2 7/8" API REG	ROC	106.1
89	8.8	6000	2 3/8" IF	ROC	105.6
102	6.3	4000	2 7/8" API REG	ROC	75.8
102	6.3	5000	2 7/8" API REG	ROC	90.6
102	6.3	6000	2 7/8" API REG	ROC	105.4
102	8.8	4000	2 7/8" API REG	ROC	94.4
102	8.8	5000	2 7/8" API REG	ROC	114.5
102	8.8	6000	2 7/8" API REG	ROC	134.6
114	6.3	4000	3 1/2" API REG	ROC	87.6
114	6.3	5000	3 1/2" API REG	ROC	104.4
114	6.3	6000	3 1/2" API REG	ROC	121.2
114	8.8	4000	3 1/2" API REG	ROC	109.2
114	8.8	5000	3 1/2" API REG	ROC	132.1
114	8.8	6000	3 1/2" API REG	ROC	155
127	6.3	5000	3 1/2" API REG	ROC	122.9
127	6.3	6000	3 1/2" API REG	ROC	141.7
127	8.8	5000	3 1/2" API REG	ROC	153.4
127	8.8	6000	3 1/2" API REG	ROC	179.1
127	12.5	5000	3 1/2" API REG	ROC	198.4
127	12.5	6000	3 1/2" API REG	ROC	233.7
140	8.8	5000	4 1/2" API REG	ROC	166.8
140	8.8	6000	4 1/2" API REG	ROC	195.2
140	12.5	5000	4 1/2" API REG	ROC	216.9
140	12.5	6000	4 1/2" API REG	ROC	256.1

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

ATLAS COPCO

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
ATLAS COPCO					
T4 (DM30/45/50, T4. RD20)					
102	8.8	7620	2 7/8" API REG	T4	168.5
102	8.8	9144	2 7/8" API REG	T4	199.2
102	19	8077	2 7/8" API REG	T4	301
102	19	9144	2 7/8" API REG	T4	338
114	8.8	6096	2 7/8" IF	T4	151.3
114	8.8	6096	3 1/2" API REG	T4	154.3
114	8.8	7620	2 7/8" IF	T4	186.2
114	8.8	7620	3 1/2" API REG	T4	189.2
114	8.8	9144	2 7/8" IF	T4	221.1
114	8.8	9144	3 1/2" API REG	T4	224.1
114	8.8	9144	3" BECO	T4	225.7
114	12.5	6553	3 1/2" API REG	T4	219.3
114	12.5	7620	3 1/2" API REG	T4	250.6
114	12.5	9144	3 1/2" API REG	T4	298.4
114	12.5	10668	3 1/2" API REG	T4	346.3
114	16	6553	3 1/2" API REG	T4	264.9
114	16	8534	3 1/2" API REG	T4	341.8
114	19	7620	3 1/2" API REG	T4	360.2
114	19	8077	3 1/2" API REG	T4	381.5
114	19	9144	3 1/2" API REG	T4	428.8
114	19	10668	3 1/2" API REG	T4	499.7
127	8.8	6553	3 1/2" API REG	T4	190.5
127	8.8	7620	3 1/2" API REG	T4	214.4
127	8.8	9144	3 1/2" API REG	T4	253.6
127	8.8	9144	3 1/2" BECO	T4	256.3
127	12.5	6553	3 1/2" API REG	T4	249.8
127	12.5	6553	3 1/2" BECO	T4	250.4
127	12.5	7620	3 1/2" API REG	T4	282.2
127	12.5	7620	3 1/2" BECO	T4	286.7
127	12.5	8077	3 1/2" API REG	T4	303.6
127	12.5	8077	3 1/2" BECO	T4	304.2
127	12.5	9144	3 1/2" API REG	T4	336
127	12.5	9144	3 1/2" BECO	T4	340.5
127	12.5	10668	3 1/2" API REG	T4	389.8
127	12.5	10668	3 1/2" BECO	T4	394.3
127	19	6553	3 1/2" API REG	T4	364

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

ATLAS COPCO

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
ATLAS COPCO					
T4 (DM30/45/50, T4. RD20)					
127	19	6553	3 1/2" BECO	T4	366.5
127	19	7620	3 1/2" API REG	T4	414.1
127	19	7620	3 1/2" BECO	T4	418.7
127	19	8077	3 1/2" API REG	T4	444.6
127	19	8077	3 1/2" BECO	T4	446.6
127	19	9144	3 1/2" API REG	T4	494.7
127	19	9144	3 1/2" BECO	T4	499.3
127	19	10668	3 1/2" API REG	T4	575.3
127	19	10668	3 1/2" BECO	T4	579.9
140	12.5	6299	4"FH	T4	273
140	12.5	6299	3 1/2" BECO	T4	277.5
140	12.5	7620	4"FH	T4	319.8
140	12.5	7620	3 1/2" BECO	T4	325
140	12.5	7823	3 1/2" BECO	T4	337.3
140	12.5	9144	4"FH	T4	384.4
140	12.5	9144	3 1/2" BECO	T4	389
140	12.5	10668	3 1/2" BECO	T4	444.5
140	19	6299	3 1/2" BECO	T4	398.4
140	19	7620	3 1/2" BECO	T4	472.3
140	19	8077	3 1/2" BECO	T4	499.3
140	19	9144	3 1/2" BECO	T4	562.2
140	19	10668	3 1/2" BECO	T4	652.2
140	25	6300	3 1/2" BECO	T4	464.5
140	25	7620	3 1/2" BECO	T4	554
140	25	9144	3 1/2" BECO	T4	661.8



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA


SANDVIK

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
SANDVIK					
DI (TITON/BPI)					
76	4	3000	2 3/8" API REG	/	33.2
76	6.3	3000	2 3/8" API REG	/	42.6
76	6.3	4000	2 3/8" API REG	/	53.4
76	6.3	5000	2 3/8" API REG	/	64.2
76	6.3	6000	2 3/8" API REG	/	75
76	8.8	5000	2 3/8" API REG	/	80.8
76	8.8	6000	2 3/8" API REG	/	95.4
89	4	3000	2 3/8" API REG	/	45.6
89	4	4000	2 3/8" API REG	/	54
89	6.3	4000	2 3/8" API REG	/	68.6
89	6.3	5000	2 3/8" API REG	/	81.4
89	6.3	6000	2 3/8" API REG	/	94.2
89	6.3	7500	2 3/8" API REG	/	113.4
89	8.8	4000	2 3/8" API REG	/	79.3
89	8.8	5000	2 3/8" API REG	/	95.2
89	8.8	6000	2 3/8" API REG	/	111.2
89	8.8	7500	2 3/8" API REG	/	135.1
102	6.3	4000	2 7/8" API REG	/	83.4
102	6.3	5000	2 7/8" API REG	/	98
102	6.3	6000	2 7/8" API REG	/	112.6
102	6.3	7500	2 7/8" API REG	/	134.8
102	8.8	4000	2 7/8" API REG	/	102
102	8.8	5000	2 7/8" API REG	/	122.1
102	8.8	6000	2 7/8" API REG	/	142.3
102	8.8	7500	2 7/8" API REG	/	172.5
114	6.3	4000	3 1/2" API REG	/	97.4
114	6.3	5000	3 1/2" API REG	/	114.2
114	6.3	6000	3 1/2" API REG	/	131
114	6.3	7500	3 1/2" API REG	/	156.2
114	8.8	4000	3 1/2" API REG	/	118.1
114	8.8	5000	3 1/2" API REG	/	141
114	8.8	6000	3 1/2" API REG	/	163.9
114	8.8	7500	3 1/2" API REG	/	198.2
127	6.3	5000	3 1/2" API REG	/	134.2
127	6.3	6000	3 1/2" API REG	/	53
127	6.3	7500	3 1/2" API REG	/	181.2

MATERIEL DE FORAGE

www.nouvelle-zema.com

SANDVIK

[illegible]

MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

HAUSHERR

DIA.EXT OUTER D. (mm)	EPAISSEUR WALL (mm)	LG LENGTH (mm)	FILETAGES THREAD	PLATS FLATS (mm)	POIDS WEIGHT (kg)
HAUSHERR					
70	6.3	4000	HAUS 2"	/	45.3
70	8.8	3000	HAUS 2"	/	44.3
70	8.8	4000	HAUS 2"	/	57.6
76	6.3	3000	2 3/8" API REG	/	38.9
76	6.3	3000	2 3/8" RS	/	39.5
76	6.3	4000	2 3/8" API REG	/	49.7
76	6.3	4000	2 3/8" RS	/	50.3
76	6.3	5000	2 3/8" API REG	/	60.5
76	6.3	5000	2 3/8" RS	/	61.1
76	6.3	6000	2 3/8" API REG	/	71.3
76	6.3	6000	2 3/8" RS	/	71.9
76	8.8	3000	2 3/8" API REG	/	48.8
76	8.8	3000	2 3/8" RS	/	49.5
76	8.8	4000	2 3/8" API REG	/	63.4
76	8.8	4000	2 3/8" RS	/	64.1
76	8.8	4000	GG2"	/	63.7
76	8.8	5000	2 3/8" API REG	/	78
76	8.8	5000	2 3/8" RS	/	78.7
76	8.8	6000	2 3/8" API REG	/	92.6
76	8.8	6000	2 3/8" RS	/	93.3
76	8.8	6000	GG2"	/	92.9
89	6.3	3000	2 3/8" API REG	/	48.7
89	6.3	4000	2 3/8" API REG	/	61.5
89	6.3	5000	2 3/8" API REG	/	74.3
89	6.3	6000	2 3/8" API REG	/	87.1
89	8.8	3000	2 3/8" API REG	/	59.5
89	8.8	4000	2 3/8" API REG	/	75.5
89	8.8	5000	2 3/8" API REG	/	91.5
89	8.8	6000	2 3/8" API REG	/	107.5
114	8.8	3000	3 1/2" API REG	/	84
114	8.8	4500	3 1/2" API REG	/	118
114	8.8	6000	3 1/2" API REG	/	159



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

ACCESOIRES ET RACCORDS ACCESSORIES/ ADAPTERS



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

RACCORDS GUIDE / GUIDE SLEEVES

MESURES / MEASUREMENTS (mm)									
FIL FEMELLE THREAD BOX	FIL MALE THREAD PIN (B)	LONGUEUR LENGTH	OD1	OD2	OD3	ID	A (PLATS) A (FLATS)	B	C
2 3/8" REG	2 3/8" REG	225	89	89	101	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	114	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	127	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	139	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	151	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	164	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	170	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	177	34	65	40	15
2 3/8" REG	2 3/8" REG	350	89	89	177	30	65	40	20
2 3/8" REG	2 3/8" REG	225	89	89	179	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	202	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	207	34	65	40	15
2 3/8" REG	2 3/8" REG	225	89	89	235	34	65	40	15
2 3/8" IF	2 3/8" IF	225	89	89	151	43	65	40	20
3 1/2" REG	3 1/2" REG	250	114	114	139	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	139	43	95	50	15
3 1/2" REG	3 1/2" REG	600	114	114	139	43	95	50	15
3 1/2" REG	3 1/2" REG	250	114	114	151	43	95	50	15
3 1/2" REG	2 3/8" REG	300	114	114	151	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	114	156	30	65	40	15
3 1/2" REG	3 1/2" REG	250	114	114	164	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	164	43	95	50	15
3 1/2" REG	3 1/2" REG	600	114	114	164	43	95	50	15
3 1/2" REG	3 1/2" REG	250	114	114	177	43	95	50	15
3 1/2" REG	2 3/8" REG	300	114	114	177	30	65	40	15
3 1/2" REG	3 1/2" REG	250	114	114	179	43	95	50	15
3 1/2" REG	3 1/2" REG	250	114	114	185	43	95	50	15
3 1/2" REG	3 1/2" REG	250	114	114	189	43	95	50	15
3 1/2" REG	3 1/2" REG	250	114	114	200	43	95	50	15
3 1/2" REG	2 3/8" REG	300	114	114	200	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	114	202	30	65	40	15
3 1/2" REG	3 1/2" REG	250	114	114	202	43	95	50	15
3 1/2" REG	3 1/2" REG	250	114	114	214	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	247	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	250	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	255	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	295	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	300	43	95	50	15



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

RACCORDS GUIDE / GUIDE SLEEVES

MESURES / MEASUREMENTS (mm)									
FIL FEMELLE THREAD BOX	FIL MALE THREAD PIN (B)	LONGUEUR LENGTH	OD1	OD2	OD3	ID	A (PLATS) A (FLATS)	B	C
3 1/2" REG	3 1/2" REG	300	114	114	302	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	325	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	334	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	343	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	348	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	375	43	95	50	15
3 1/2" REG	3 1/2" REG	300	114	114	475	43	95	50	15
4 1/2" REG	4 1/2" REG	317	140	140	216	58	120	50	20
4 1/2" REG	4 1/2" REG	317	140	140	247	58	120	50	20
4 1/2" REG	4 1/2" REG	317	140	140	255	58	120	50	20
4 1/2" REG	4 1/2" REG	317	140	140	295	58	120	50	20
4 1/2" REG	4 1/2" REG	317	140	140	305	58	120	50	20
4 1/2" REG	4 1/2" REG	317	140	140	330	58	120	50	20
4 1/2" REG	4 1/2" REG	317	140	140	376	58	120	50	20
6 5/8" REG	6 5/8" REG	318	197	197	305	58	178	50	50
6 5/8" REG	6 5/8" REG	318	197	197	310	43	178	50	15
6 5/8" REG	6 5/8" REG	318	197	197	375	43	178	50	15
3 1/2" REG	2 3/8" REG	300	114	89	139	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	89	164	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	89	182	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	89	189	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	89	202	30	65	40	15
3 1/2" REG	2 3/8" REG	300	114	89	205	30	65	40	15
4 1/2" REG	3 1/2" REG	235	146	114	202	43	95	50	15
4 1/2" REG	3 1/2" REG	420	146	114	212	43	95	50	25
4 1/2" REG	3 1/2" REG	235	146	114	219	43	95	50	15
4 1/2" REG	3 1/2" REG	235	146	114	247	43	95	50	15
4 1/2" REG	3 1/2" REG	235	146	114	255	43	95	50	15
4 1/2" REG	3 1/2" REG	235	146	114	295	43	95	50	15
4 1/2" REG	3 1/2" REG	235	146	114	330	43	95	50	15
4 1/2" REG	3 1/2" REG	235	146	114	350	43	95	50	15
4 1/2" REG	3 1/2" REG	235	146	114	385	43	95	50	15



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

RACCORDS GUIDE HELICOIDALE / SPIRAL GUIDE SLEEVES

MESURES / MEASUREMENTS (mm)										
FIL FEMELLE (A) THREAD BOX (A)	FIL MALE (B) THREAD PIN (B)	LONGUEUR LENGTH	OD1	OD2	ID	A (PLATS) A (FLATS)	B	C1	C2	POIDS KG WEIGHT KG
2 3/8" REG	2 3/8" REG	500	76	113	30	65	40	90	17	18
2 3/8" REG	2 3/8" REG	500	76	114	30	65	40	90	17	19
2 3/8" REG	2 3/8" REG	500	89	139	30	65	40	90	17	27
2 3/8" REG	2 3/8" REG	500	89	162	30	65	40	90	17	29
2 3/8" REG	2 3/8" REG	1000	89	120	30	65	40	90	17	53
3 1/2" REG	3 1/2" REG	500	114	162	38	95	50	110	20	44
4 1/2" REG	4 1/2" REG	700	140	250	58	120	50	105	20	102
6 5/8" REG	6 5/8" REG	600	194	304	80	152	70	160	70	130



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

TARAUDS / FISHING TOOLS CLOCHES / FISHING OVERSHOT

MESURES / MEASUREMENTS (mm)			
FIL MALE (B) THREAD PIN (B)	OD	OD2	OD3
2 3/8" REG	76	113	30
3 1/2" REG	76	114	30
3 1/2" REG	89	139	30
4 1/2" REG	89	162	30
6 5/8" REG	89	120	30



MATERIEL DE FORAGE

www.nouvelle-zema.com



ZEMA

NOTES

Lined area for notes.

MATERIEL DE FORAGE

www.nouvelle-zema.com